## **AMENDMENTS TO THE CLAIMS**

- 1. (Currently Amended) A door mirror set plate comprising:
- a synthetic resin base plate attached to a vehicle;
- a cylindrical support shaft which is vertically provided on the base plate integrally therewith and rotatively supports a door mirror body storing a mirror plate; and
- a curved surface section which is embedded around <u>a base of</u> the support shaft <del>base</del> on the base plate;

wherein the curved surface section and curvedly connects between an external surface of the support shaft with and a top surface of the base plate, and

wherein the curved surface section is disposed below the top surface of the base plate thereof.

- 2. (Original) The door mirror set plate according to claim 1, wherein the curved surface section is formed like a groove at an outside periphery of the support shaft base.
- 3. (Currently Amended) The door mirror set plate according to claim 1, wherein there is provided a flat section <u>for supporting a thrust washer</u> which is formed at an outside periphery of the support shaft base on the top surface of the base plate at the same level as the top surface of the base plate and <u>which</u> connects between the external surface of the support shaft and the top surface of the base plate by crossing the curved surface section.
- 4. (Original) The door mirror set plate according to claim 3, wherein the flat section is formed radially on an outside periphery of the support shaft base.

Claims 5-15. (Canceled)

16. (Original) The door mirror set plate according to claim 1, wherein, the door mirror set plate is formed of glass fiber reinforced polyamide.

Claims 17-18. (Canceled)